# **STOCKCHASER** *The stock to dock product solution*



Photos may be shown with optional equipment



Taylor-Dunn's Stockchaser is a cost effective solution to improve efficiency in any warehousing application. This unique narrow aisle, highly maneuverable vehicle provides an ergonomic advantage by quickly bringing the operator closer to stock when order picking.

#### **Features**

- 24, 36 or 48 volt drive system
- 170 cm turning radius
- Zero emissions
- Regenerative braking (SC-100 only)
- 75 x 147 cm deck size
- Customisable to fit your application





# **STOCKCHASER**


#### Performance

Performance	SC-090	SC-100
LOAD CAPACITY	408 kg	454 kg
MAX SPEED	14 km / h	13 km / h
TOW CAPACITY	907 kg*	2268 kg*
TURNING RADIUS	170 cm	170 cm

\*Based on Standard Configuration: Actual towing capacity is dependent on application, vehicle configuration, ballast weight, and operating environment.

# Dimensions

OVERALL LENGTH	218 cm
OVERALL WIDTH	75 cm
HEIGHT	123 cm
WHEEL BASE	120 cm
DECK SIZE	75 x 147 cm
DECK HEIGHT	64 cm



61.6 cm → 74.9 cm · R170.1 cm

# Power supply / Drive train

MOTOR	SC-090 (Series) -24: 3.8 hp, SC-100 (Separately Excited) -24: 4.3 hp, -36: 6.6 hp, -48: 8.8 hp
SYSTEM VOLTAGE	24, 36, and 48 Volt
TRANSMISSION	SC-090: Direct Gear Drive, SC-100: GT Automotive Type Differential
BATTERIES	210 Amp-hour, 6 Volt, Lead Acid
CHARGER	<b>SC-090-24 &amp; SC-100-24:</b> Built-in, 600 Watt, 110 VAC Automatic w/ Interlock <b>SC-100-36:</b> Built-in, 1kW, w/ Interlock, <b>SC-100-48:</b> Built-in, 1kW, 60 Hz, w/ Interlock, 110 VAC
CONTROLLER	Solid State Speed Controller, Regenerative Braking

### Chassis

FRAME	Fully Welded, Unitised, 16 Gauge, Diamond Plate Steel Body	
STEERING	Manual, Chain Linkage, Front Fork, Clover Leaf Steering Wheel	State -
SUSPENSION	Solid Mounted Rear Axle	1 P TOOL
BRAKES	Hand-Operated Parking Brake SC-090: Rear Drum, SC-100: Rear Disc	( a million
TYRES	4.80 x 8 Load Range B Pneumatic	
		GT Automotive Drive

# General

UNIT WEIGHT	SC-090: 760 (345) SC-100-24: 970 (440) SC-100-36: 1095 (497) SC-100-48: 1195 (542)
OPERATOR COMFORT	Padded Backrest
INSTRUMENTATION	<b>SC-090:</b> Battery Status Indicator, F-N-R Switch, Key Switch, Electric Horn <b>SC-100:</b> Smart View Display, F-N-R Switch, Reverse Alarm, DC/DC Converter, Electric Horn
CONFORMANCE	Type E OSHA 1910.178, ANSI B56.8

# Options

- Strobe light
- Head light / taillight
- Round steering wheel
- Knee pad, comfort kit
- Hour meter (sc-90 only)
- 4, 5 or 6 step ladder

Diamond plate deck

- Portable charger
- Strobe light on a pole
- Soft solid tyres
- Solid cushion tyres
- Dual front fork
- Wider deck
- Clipboard holder
- Second level deck
- Lift-out battery box
- Roll-out battery box
- 225, 260 Amp-hour battery

(SC-100 only)

- Various hitches
- Smooth skin frame
- Tie downs



1800 425 438

ျား www.toyotamaterialhandling.com.au



Toyota Material Handling Australia (TMHA) has used its best endeavours to ensure brochure information is correct when published. All images are used for illustration purposes only and actual colour of products may differ from images displayed. TMHA, to the extent permissible at law, is not liable to any person for loss or damage arising from reliance upon information contained in this brochure. Distributed nationally by Toyota Material Handling Australia Pty Limited ABN 38 104 644 635. 8 Secombe Place Moorebank NSW 2170. Printed April 2019.